

## Telescopic Cylinder HFJ 10/30 G 4

Single acting, gravity return telescopic cylinder. Supplied with 30 cm connecting hose with anti-kink spring and High Flow female coupler, A 118.

### Standard supplied with:

- High Flow female coupler A 118
- HFJ 10/30 G 4 contains a 30 cm connecting hose with anti-kink spring
- HJ 20/50 G 11 contains a flat saddle

## Specifications

### Specifications

Details		
Article number	100.111.005	
Basic specifications		
Model	HFJ 10/30 G 4	
Max. working pressure	720 / 72 (bar/Mpa)	10443 psi
Performance		
Tonnage	10 t	22046 lb
Stroke	41 mm	1.6 in
Stroke 1st plunger	21 mm	0.8 in
Stroke 2nd plunger	20 mm	0.8 in
Closed height	49 mm	1.9 in
Capacity 1st plunger	318 / 32.4 (kN/t)	71489 lbf
Capacity 2nd plunger	99.7 / 10.2 (kN/t)	22413 lbf
Effective pressure area 1st plunger	44.2 cm <sup>2</sup>	6.9 sq. in.
Effective pressure area 2nd plunger	13.9 cm <sup>2</sup>	2.2 sq. in.
General specifications		
Required oil content (effective)	118 cc	4 oz
Connection	A 118	
Hose		
Cylinder type		

This site uses cookies to store information on your computer. Some of these cookies are essential to make our site work. Others help us to improve by giving us some insight into how the site is being used or help to improve the experience of using our site. By using our site you accept the terms of our privacy policy (</paginas/3842-privacy-policy.html>)

Allow cookies